

## RM Cylinders ERP Data Stelflow Direct Electric WaterHeaters

Manufacturer	Model	Type	Production Code	Capacity	Standing Heat Loss of Vessel	Standing Heat Loss of Vessel	ERP Energy Banding	ERP Tapping Profile	Temperature Set	ERP Energy Efficiency	Daily Energy Usage Qelec	Yearly Energy Usage AFC	Yearly Energy Usage AEC	Off Peak Usage	Noise Level
				Litre	KWH/24H	Watts	A-G		°C	ηwh (%)	kWH/Day	kWH/Year	GJ/Year	Yes/No	DB
RM Cylinders	Stelflow	Direct	S90D	90	0.96	40	C	M	60	38	6.990	1535	6	No	15
RM Cylinders	Stelflow	Direct	S120D	120	1.11	46	C	M	60	38	7.290	1601	6	No	15
RM Cylinders	Stelflow	Direct	S150D	150	1.26	53	C	M	60	38	7.370	1618	6	No	15
RM Cylinders	Stelflow	Direct	S180D	180	1.40	58	C	L	60	38	13.202	2899	10	No	15
RM Cylinders	Stelflow	Direct	S210D	210	1.48	62	C	L	60	37	13.970	3068	11	No	15
RM Cylinders	Stelflow	Direct	S250D	250	1.76	73	C	XL	60	38	21.007	4562	16	No	15
RM Cylinders	Stelflow	Direct	S300D	300	2.03	85	C	XL	60	38	21.204	4656	17	No	15