

150 L Indirect Slimline

Capacity	Type	Model	Installation
150L	Unvented	Indirect	Floor Standing

Descriptive Specification

- The unit is to be floor standing Stelflow pre-insulated pressurised Hot Water Cylinder.
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 52 W.

Constructive Specifications

Capacity	150L
Cylinder Material	Stainless Steel Duplex LDX 2101
Thermal Insulation	Polyurethane foam CFC-Free and HCFC Free
Casing	Painted Galvanised Carbon Steel DX51D
Coil Material	Stainless Steel Tube AISI 316L
Weight (empty) kg	38
Weight (full) kg	177
Max. Operating Pressure (bar)	5
Test Pressure (Bar)	10
Max. Working Temperature (c)	90
Heating Elements	1. No Incoloy Immersion
Unvented Kit Components	Expansion Vessel, Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish
Height (mm)	1430
Diameter (mm)	475
Immersion Reheat (mins)	107
Indirect Reheat (mins)	23
Heat Exchanger (kw)	16.33
Standing Loss (kWh/day)	1.44
Product Code	TRSMVI0150SFC
ErP Band	C

Dimensions

	Product	150IS
A	Cold Inlet	162
B	Cottom Coil	328
C	Immersion 1	418
D	Stat Pocket	433
E	Secondary Return	-
F	T&P Valve	1527

